

Technické parametry postřikovače PRO SPORT							
TRYSKA	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	PRŮTOK	SRÁŽKOVÁ VYDATNOST	SRÁŽKOVÁ VYDATNOST
	[bar]	[m]	[l/s]	[l/min]	[m ³ /hod]	■ - mm/hod]	▲ - mm/hod]
5	3,0	13,7	0,322	19,3	1,16	12,0	15,0
	3,5	14,3	0,372	22,3	1,34	13,0	16,0
	4,0	14,3	0,410	24,6	1,48	14,0	17,0
	5,0	14,9	0,448	26,9	1,61	14,0	17,0
10	3,5	16,2	0,668	40,1	2,41	18,0	22,0
	4,0	15,9	0,745	44,7	2,68	21,0	25,0
	5,0	16,2	0,795	47,7	2,86	22,0	26,0
	5,5	16,8	0,852	51,1	3,07	22,0	26,0
15	3,5	17,4	0,820	49,2	2,95	20,0	23,0
	4,0	18,0	0,897	53,8	3,23	20,0	24,0
	5,0	18,0	0,972	58,3	3,50	22,0	26,0
	5,5	19,2	1,042	62,5	3,75	20,0	24,0
20	4,0	19,8	1,192	71,5	4,29	22,0	26,0
	5,0	20,4	1,293	77,6	4,66	22,0	27,0
	5,5	21,0	1,382	82,9	4,97	23,0	27,0
	6,0	21,6	1,463	87,8	5,27	23,0	27,0
25	4,0	20,4	1,438	86,3	5,18	25,0	30,0
	5,0	21,6	1,565	93,9	5,63	24,0	29,0
	5,5	22,9	1,672	100,3	6,02	23,0	28,0
	6,0	23,5	1,690	101,4	6,08	22,0	26,0
30	4,0	20,4	1,495	89,7	5,38	26,0	31,0
	5,0	21,0	1,615	96,9	5,81	26,0	31,0
	5,5	21,0	1,735	104,1	6,25	28,0	34,0
	6,0	21,6	1,842	110,5	6,63	28,0	34,0

srážková vydatnost je počítána pro výšeč 180°, pro celokruh dělte 2, pro čtvrtkruh násobte 2.