













## Rotační trysky nastavitelné

RN100 90°-270° zelená 							RN100 360° zelená světle 						
ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲	ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲
[°]	[bar]	[m]	[l/s]	[l/min]			[°]	[bar]	[m]	[l/s]	[l/min]		
90°	2,07	4,0	0,014	0,83	13,00	15,00	360°	2,07	4,0	0,056	3,33	13,00	15,00
	2,41	4,3	0,015	0,91	12,00	14,00		2,41	4,3	0,059	3,56	12,00	13,50
	2,76	4,3	0,016	0,95	12,00	14,00		2,76	4,3	0,063	3,78	12,50	14,50
	3,10	4,6	0,018	1,06	12,00	14,00		3,10	4,6	0,073	4,35	12,50	14,50
	3,45	4,6	0,019	1,14	13,00	15,00		3,45	4,6	0,076	4,54	13,00	15,00
180°	2,07	4,0	0,028	1,67	13,00	15,00							
	2,41	4,3	0,030	1,78	12,00	13,00							
	2,76	4,3	0,032	1,89	12,00	14,00							
	3,10	4,6	0,037	2,20	13,00	15,00							
	3,45	4,6	0,038	2,27	13,00	15,00							
270°	2,07	4,0	0,042	2,50	13,00	15,00							
	2,41	4,3	0,045	2,69	12,00	14,00							
	2,76	4,3	0,047	2,84	12,00	14,00							
	3,10	4,6	0,056	3,33	13,00	15,00							
	3,45	4,6	0,057	3,41	13,00	15,00							

RN200 90°-270° modrá 							RN200 360° modrá světle 						
ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲	ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲
[°]	[bar]	[m]	[l/s]	[l/min]			[°]	[bar]	[m]	[l/s]	[l/min]		
90°	2,07	4,9	0,022	1,29	13,00	15,00	360°	2,07	4,9	0,085	5,07	13,0	15,0
	2,41	5,2	0,024	1,44	13,00	15,00		2,41	5,2	0,095	5,68	13,0	15,0
	2,76	5,5	0,026	1,55	12,50	14,50		2,76	5,5	0,104	6,25	12,5	14,5
	3,10	5,8	0,027	1,59	11,50	13,00		3,10	5,8	0,106	6,36	13,0	15,0
	3,45	5,8	0,030	1,78	13,00	15,00		3,45	5,8	0,119	7,12	14,0	16,0
180°	2,07	4,9	0,042	2,54	13,00	15,00							
	2,41	5,2	0,047	2,84	13,00	15,00							
	2,76	5,5	0,052	3,14	12,50	14,50							
	3,10	5,8	0,053	3,18	11,50	13,00							
	3,45	5,8	0,059	3,56	13,00	15,00							
270°	2,07	4,9	0,064	3,82	13,00	15,00							
	2,41	5,2	0,071	4,28	13,00	15,00							
	2,76	5,5	0,078	4,69	12,50	14,50							
	3,10	5,5	0,080	4,77	13,00	15,00							
	3,45	5,8	0,089	5,34	13,00	15,00							

RN300 90°-270° šedá 							RN300 360° šedá světle 						
ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲	ÚHEL	TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK	■	▲
[°]	[bar]	[m]	[l/s]	[l/min]			[°]	[bar]	[m]	[l/s]	[l/min]		
90°	2,07	7,9	0,051	3,03	11,0	13,0	360°	2,07	7,9	0,196	11,73	11,0	13,0
	2,41	7,9	0,054	3,22	12,0	12,5		2,41	8,2	0,202	12,11	11,0	12,5
	2,76	8,2	0,057	3,41	12,0	12,5		2,76	8,5	0,221	13,25	11,0	13,0
	3,10	8,5	0,060	3,60	11,0	13,0		3,10	8,5	0,224	13,44	11,0	13,0
	3,45	8,5	0,063	3,79	11,5	13,0		3,45	9,2	0,234	14,01	11,0	12,5
180°	2,07	7,9	0,088	5,30	11,0	13,0							
	2,41	8,2	0,095	5,68	11,0	12,5							
	2,76	8,2	0,101	6,06	11,5	12,5							
	3,10	8,9	0,107	6,44	10,5	12,0							
	3,45	9,2	0,114	6,81	10,0	11,5							
270°	2,07	7,9	0,155	9,27	11,0	13,0							
	2,41	8,2	0,161	9,65	10,5	12,5							
	2,76	8,5	0,174	10,41	11,0	13,0							
	3,10	8,5	0,183	10,98	11,0	13,0							
	3,45	8,2	0,196	11,73	12,5	14,0							

		TLAK	DOSTŘÍK	PRŮTOK	PRŮTOK
		[bar]	[m]	[l/s]	[l/min]
RN RS 		2,06	4x15	0,019	1,14
		2,46	5x15	0,020	1,21
		2,75	5x15	0,022	1,32
		3,10	6x16	0,024	1,43
		3,45	6x16	0,025	1,51
RN LS 		2,06	4x15	0,019	1,14
		2,46	5x15	0,020	1,21
		2,75	5x15	0,022	1,32
		3,10	6x15	0,024	1,43
		3,45	6x16	0,025	1,51
RN SS 		2,06	4x29	0,030	1,80
		2,46	5x30	0,035	2,08
		2,75	5x30	0,038	2,30
		3,10	6x31	0,041	2,46
		3,45	7x32	0,044	2,64

Dostřik lze zredukovat o 25%. Tabulkové hodnoty reprezentují výsledky testů při nulovém větru.